

MATERIAL SAFETY DATA SHEET

DAUBERT CHEMICAL COMPANY

4700 SOUTH CENTRAL AVENUE
CHICAGO, ILLINOIS 60638
TELEPHONE: (708) 496-7350
FAX: (708) 496-7367

EMERGENCY CONTACT:
CHEMTREC (800) 424-9300

HMIS HAZARD RATING

Health	1
Fire	2
Reactivity	0
Personal Protection	D

Date of Review: May 6, 2010

Revised:

Date of Preparation: December 20, 2006

By: R. Lauterbach

SECTION I: PRODUCT IDENTIFICATION

Product Name: **Nox-Rust® 1553**
General or Generic ID: PETROLEUM BASED RUST PREVENTATIVE

SECTION II: HAZARDOUS INGREDIENTS

Component	Wt%	Recommended Exposure Limits (TWA)
Aliphatic Hydrocarbons (Stoddard Type) CAS # 8052-41-3	35-45	OSHA PEL: 100 ppm ACGIH TLV: 100 ppm
Talc CAS #14807-96-6	1-11	OSHA PEL: 2 mg/m ³ (resp. dust) ACGIH TLV: 2 mg/m ³ (resp. dust)
Hydrotreated Heavy Naphthenic Distillate CAS #64742-52-5	1-9	None Established
Calcium Petroleum Sulfonate CAS #61789-86-4	1-8	None Established

SECTION III: HEALTH HAZARD INFORMATION

Eye: Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

Skin: Can cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, burns and other skin damage. Additional symptoms of skin contact may include:

allergic skin reaction (delayed skin rash which may be followed by blistering, scaling and other skin effects)

Swallowing: Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can enter the lungs during swallowing or vomiting and cause lung inflammation and/or damage.

Inhalation: Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful.

Symptoms of Exposure: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), and death.

Target Organ Effects: Overexposure to this material (or its components) has been suggested as a cause of the

following effects in humans, and may aggravate preexisting disorders of these organs: central nervous system effects.

Developmental Information: No data

Cancer Information: No data

Other Health Effects: No data

Primary Route(s) of Entry: Inhalation, Skin contact.

SECTION IV: FIRST AID PROCEDURES

Eyes: If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

Skin: Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Swallowing: Do not induce vomiting. This material is an aspiration hazard. If individual is drowsy or unconscious, place on left side with the head down. Seek medical attention. If possible, do not leave individual unattended.

Inhalation: No data

Note to Physicians: No data

SECTION V: FIRE AND EXPLOSION HAZARD DATA

Flash Point: > 104 °F (40 °C) PMCC

Explosive Limit: (for component) Lower 1.0 Upper 7.0 %

Autoignition Temperature: No data

Hazardous Products of Combustion: May form: carbon dioxide and carbon monoxide.

Fire and Explosion Hazards: Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, other flames and ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively

Extinguishing Media: regular foam, carbon dioxide, dry chemical.

Fire Fighting Instructions: Water or foam may cause frothing which can be violent and possibly endanger the life of the firefighter. Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this EISFS.

SECTION VI: SPECIAL PRECAUTIONS AND SPILL/LEAK PROCEDURES

Small Spill: Absorb liquid on vermiculite, floor absorbent or other absorbent material.

Large Spill: Prevent run-off to sewers, streams or other bodies of water. If run-off occurs notify proper authorities as required that a spill has occurred. Eliminate all ignition sources (flares, flames, including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Scoop into containers.

SECTION VII: SAFE HANDLING INFORMATION

Handling: Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor liquid, and/or solid), all hazard precautions given in the data sheet must be observed. All five gallon pails and larger metal containers including tank cars and tank trucks should be grounded and/or bonded when material is transferred.

Storage: Not applicable

SECTION VIII: EXPOSURE CONTROLS

Eye Protection: Chemical splash goggles in compliance with OSHA regulations are advised however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

Skin Protection: Wear resistant gloves such as: neoprene. To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

Respiratory Protections: If workplace exposure limit(s) of product or any component is exceeded (See Exposure Guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (consult your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

Engineering Controls: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

SECTION IX: PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: (for component)	315 °F (157.2 °C) @ 760 mmHg
Vapor Pressure:	2 mmHg @ 68 °F
Specific Vapor Density:	No data
Specific Gravity:	.97 @ 77 °F
Liquid Density:	8.1 lbs/gal @ 60 °F
Percent Volatiles (Including Water):	41-43
Evaporation Rate:	SLOWER THAN ETHYL ETHER
Appearance:	Translucent
State:	LIQUID
Physical Form:	No data
Color:	Amber
Odor:	No data
pH:	Not Applicable
Viscosity:	4000-8000 cps @ #5 spindle @ 10 rpm

SECTION X: REACTIVITY HAZARD DATA

Hazardous Polymerization: Product will not undergo hazardous polymerization.

Hazardous Decomposition: May form: carbon dioxide and carbon monoxide.

Chemical Stability: Stable.

Incompatibility: Avoid contact with strong oxidizing agents.

SECTION XI: TOXICOLOGICAL INFORMATION

None known.

SECTION XII: ECOLOGICAL INFORMATION

None known.

SECTION XIII: DISPOSAL CONSIDERATIONS

Waste Management Information: Dispose of in accordance with all applicable local, state and federal regulations.

SECTION XIV: TRANSPORTATION INFORMATION

***** EXORT AND AIR TRANSPORTATION *****

Totes and Tankers

UN1268, PETROLEUM DISTILLATES N.O.S., (Naphtha Solvent), 3, PGIII

Domestic by Ground (Pails, Kegs, Drums): Non-Regulated

SECTION XV: REGULATORY INFORMATION

Volatile Organic Content: (Calculated Values)

VOC per gallon: 3.4 lbs/gal

EPA Hazardous Waste Number(s) (40 CFR Part 261): N/A

EPA Hazard Category (40 CFR Part 370): IMMEDIATE (ACUTE)
FIRE

US Federal Regulations

TSCA (Toxic Substances Control Act) Status

TSCA (UNITED STATES) The intentional ingredients of this product are listed.

SARA TITLE III:

This product contains the following TOXIC CHEMICALS subject to the Reporting Requirements of Sec. 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986, and of 40 CFR Part 372:

Chemical	CAS No.	Wt%
NONE		

This product contains the following EXTREMELY HAZARDOUS SUBSTANCE(S) subject to Emergency Planning Requirements under Sec. 301-303 (40 CFR Parts 300 and 355) and Emergency Release Notification Requirements under Sec. 304:

Chemical	CAS No.	Wt%	RQ/TPQ Lbs
NONE			

This product contains the following (CERCLA LIST) HAZARDOUS SUBSTANCE(S) subject to Emergency Release Notification Requirements under Sec. 304 (40 CFR Part 302):

Chemical	CAS No.	Wt%	Final RQ Lbs
NONE			

CALIFORNIA PROPOSITION 65:

This product may contain trace quantities of the following chemicals that are identified by the State of California under the Safe Drinking Water and Toxic Reinforcement Act of 1986 ("Proposition 65") as either a carcinogenic or reproductive hazard:

Chemical	CAS No.	Estimated Concentration %
NONE		

SECTION XVI: OTHER INFORMATION

Although the information contained herein is believed to be reliable, it is furnished without warranty of any kind. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, and storage.