

# MATERIAL SAFETY DATA SHEET

## DAUBERT CHEMICAL COMPANY

4700 SOUTH CENTRAL AVENUE  
CHICAGO, ILLINOIS 60638  
TELEPHONE: (708) 496-7350  
FAX: (708) 496-7367

EMERGENCY CONTACT:  
CHEMTREC (800) 424-9300

## HMIS HAZARD RATING

HEALTH	2
FIRE	3
REACTIVITY	0
PERSONAL PROTECTION	D

Date of Review:  
Date of Preparation: April 8, 2004

Revised: January 18, 2010  
By: R. Lauterbach

## SECTION 1: PRODUCT IDENTIFICATION

Product Name: **Tectyl® 1022**  
Chemical Family: Petroleum Solvent/Asphalt Blend  
Material Usage: Corrosion Preventive Compound

**EMERGENCY OVERVIEW:** Petroleum solvent-based product with solvent odor. Flammable liquid; when product burns it releases typical hydrocarbon products of combustion. Refer to Section 3 for health effects and to Section 5 for fire hazard data.

## SECTION 2: HAZARDOUS INGREDIENTS

Component	Wt%	Recommended Exposure Limits (TWA)
<sup>1</sup> Aliphatic Petroleum Solvent CAS #64742-89-8	35-45	OSHA PEL: 300 ppm OSHA STEL: 400 ppm ACGIH TLV: 300 ppm NIOSH: 350 mg/m <sup>3</sup> (8 Hr TWA)
<sup>1</sup> Petroleum Asphalt CAS #8052-42-4	35-45	ACGIH TLV: 5 mg/m <sup>3</sup> (for fumes) NIOSH: 5 mg/m <sup>3</sup> (ceiling limit)
<sup>[1]</sup> Aromatic Petroleum Distillates CAS #64742-95-6 (59-63%)	2-7	OSHA PEL: 50 ppm ACGIH TLV: 50 ppm
<sup>[1]</sup> Carbon Black CAS #1333-86-4	0-3	AGIH TLV: 3.5 mg/m OSHA PEL: 3.5 mg/m <sup>3</sup> ( <sup>[2]</sup> nuisance dust)

<sup>[1]</sup> See Section 3

<sup>[2]</sup> This component poses a hazard only if a dust is formed, i.e., by sawing, sanding, drilling, etc.

## SECTION 3: HEALTH HAZARD INFORMATION

**Primary Routes of Entry:** Inhalation, skin absorption.

**Acute Effects:** Excessive inhalation may produce dizziness, nausea, headache, and incoordination. May cause severe eye irritation and reversible skin irritation. Prolonged skin exposure may cause dermatitis or oil acne. Breathing mists may cause dizziness or pulmonary irritation. Excessive inhalation may produce dizziness, nausea, headache, and incoordination.

**Chronic Effects:** Some asphalt solutions have produced skin cancer in laboratory animals. The activity of test materials varies widely, but the activity, in general, is weak. Based on the skin painting data, IARC has concluded that there is sufficient evidence for carcinogenicity of asphalts, diluted, dissolved, or liquefied in solvents, in laboratory animals. Workers, therefore, who practice poor personal hygiene and who are repeatedly exposed by direct skin contact to petroleum asphalts over many years, may potentially be at risk of developing skin cancer. Intermittent or occasional skin contact with petroleum asphalts is not expected to have serious health effects as long as good personal hygiene measures, such as those outlined in this Material Safety Data Sheet, are followed. In addition, asphalt vapors may contain polycyclic aromatic hydrocarbons, some of which are known to be carcinogenic. Therefore, prolonged breathing of vapors should be avoided.

**Special Remarks:**

Some asphalts may contain hydrogen sulfide (CAS #7783-06-4) ACGIH TLV = 10 ppm. Hydrogen sulfide (HS) may accumulate in storage tanks and bulk transport compartments containing asphalts. Prolonged breathing of low levels of HS will produce eye/respiratory tract irritation; extremely high levels (1000 ppm) can cause unconsciousness/death.

This aliphatic solvent naphtha (VMP) contains the following: less than 8% xylene, CAS #1330-20-7, which has a PEL/TLV of 100 ppm, STEL of 150 ppm; and less than 2% ethyl benzene, CAS #100-41-4, which has a PEL/TLV of 100 ppm, STEL of 125 ppm. Xylene and ethyl benzene are subject to the Reporting Requirements of Section 313 of Sara Title III.

**Carcinogenicity:** Asphalt solutions are considered to be animal carcinogens by IARC.

Carbon Black has been classified by IARC as a Category 2B (known animal carcinogen, possible human carcinogen) material. This was based on the results of rat inhalation studies of carbon black, despite the lack of parallel evidence on humans or other animal species.

**Pre-Existing Medical Conditions Aggravated by Exposure:** Exposure may aggravate pre-existing respiratory or skin problems.

#### SECTION 4: FIRST AID PROCEDURES

**Inhalation:** Move victim to fresh air and call emergency medical care. If not breathing, give artificial respiration; if breathing is difficult, give oxygen.

**Eyes:** In case of contact with material, immediately flush eyes with running water for at least 15 minutes. Seek immediate medical attention.

**Skin:** Wash skin with soap and water. Remove and isolate contaminated clothing and shoes at the site.

**Ingestion:** DO NOT INDUCE VOMITING. Consult a physician. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs.

#### SECTION 5: FIRE AND EXPLOSION HAZARD DATA

**Flash Point:** 50°F. Min. (COC)

**Explosive Limits:** LEL = 0.6 UEL = 7.0

**EXTINGUISHING MEDIA:** Small Fires: Dry chemical, CO<sub>2</sub>, water spray, or regular foam.

Large Fires: Water spray, fog, or regular foam. Move container from fire area if you can do it without risk. Apply cooling water to sides of containers that are exposed to flames until well after fire is out. Stay away from ends of tanks. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tank due to fire.

**Special Firefighting Protection/Emergency Action:** Fire may produce irritating or poisonous gases. Positive pressure self-contained breathing apparatus (SCBA) and structural firefighters' protective clothing will provide limited protection. Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind; keep out of low areas. If runoff from fire control occurs, notify the appropriate authorities.

**Unusual Fire/Explosion Hazards:** Flammable/combustible material; may be ignited by heat, sparks or flames. Vapors may travel to a source of ignition and flash back. Container may explode in heat of fire. Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard.

**Products of Combustion:** Carbon monoxide, carbon dioxide, oxides of sulfur, miscellaneous hydrocarbons.

#### SECTION 6: SPECIAL PRECAUTIONS AND SPILL/LEAK PROCEDURES

**Steps to be taken in case Material is Released or Spilled:** Shut off ignition sources; no flares, smoking or flames in hazard area. Stop leak if you can do it without risk.

**Small Spills:** Take up with sand or other noncombustible absorbent material and place into containers for later disposal.

**Large Spills:** Dike far ahead of liquid spill for later disposal.

## SECTION 7: SAFE HANDLING INFORMATION

**Precautions To Be Taken In Handling/Storage:** Store in cool, well-ventilated area. Keep away from flames, sparks or hot surfaces. Never use a torch to cut or weld on or near container. Empty containers can contain explosive vapors.

**Other Precautions:** Never wear contaminated clothing. Launder or dry clean before wearing. Discard oil-soaked shoes. Wash thoroughly with soap and water (waterless hand cleaner may be helpful in removing residues) after use and before smoking or eating. Avoid excessive skin contact.

## SECTION 8: EXPOSURE CONTROLS

**Respiratory Protection:** NIOSH-approved respirator for organic vapor and mist to control exposure where ventilation is inadequate.

**Ventilation:** General and local exhaust.

**Personal Protective Equipment:**

Protective Gloves: Impervious gloves (Viton, PVOH, etc.)

Eye Protection: Safety glasses with sideshields or chemical goggles.

Other Protective Clothing or Equipment: If splashing is anticipated, wear rubber apron and boots or other protective equipment to minimize contact.

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Color:	Black
Appearance:	Liquid
Odor:	Petroleum Solvent
Boiling Point (initial):	230
Evaporation Rate (n-Butyl Acetate=1):	>1
Vapor Pressure (mmHg @ 20°C):	5.2
Vapor Density (air=1):	>1
Solubility in Water:	Negligible
Specific Gravity:	0.88
pH:	Not Applicable
Percent Volatile by Volume:	57

## SECTION 10: STABILITY / REACTIVITY DATA

**Stability:** Stable

**Incompatibility:** Strong acids, oxidizing agents.

**Hazardous Decomposition Products:** Carbon monoxide, carbon dioxide, oxides of sulfur, miscellaneous hydrocarbons.

**Hazardous Polymerization:** Will not occur.

## SECTION 11: TOXICOLOGICAL INFORMATION

None known.

## SECTION 12: ECOLOGICAL INFORMATION

None known.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Methods:** Dispose of in accordance with state, local and federal regulations. Materials may become a hazardous waste through use. If permitted, incineration may be practiced. Consider recycling solvent.

**SECTION 14: TRANSPORTATION INFORMATION**

**UN 1993, FLAMMABLE LIQUIDS N.O.S.,  
(XYLENE, ETHYLBENZENE, ASPHALT, NAPHTHA SOLVENT), 3, PGII**

**SECTION 15: REGULATORY INFORMATION**

Volatile Organic Content: (Calculated Values)  
VOC per gallon: 3.7 lbs/gal  
VOC per gallon minus exempt solvents & water: 3.7 lbs/gal

EPA Hazardous Waste Number(s) (40 CFR Part 261): D001/U220

EPA Hazard Category (40 CFR Part 370): DELAYED (CHRONIC)  
FIRE (FLAMMABLE)

**SARA TITLE III:**

This product contains the following TOXIC CHEMICALS subject to the Reporting Requirements of Sec. 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986, and of 40 CFR Part 372:

Chemical	CAS No.	Wt%
Xylene	1330-20-7	<1
Ethylbenzene	100-41-4	<0.1

This product contains the following EXTREMELY HAZARDOUS SUBSTANCE(S) subject to Emergency Planning Requirements under Sec. 301-303 (40 CFR Parts 300 and 355) and Emergency Release Notification Requirements under Sec. 304:

Chemical	CAS No.	Wt%	RQ/TPQ Lbs
None			

This product contains the following (CERCLA LIST) HAZARDOUS SUBSTANCE(S) subject to Emergency Release Notification Requirements under Sec. 304 (40 CFR Part 302):

Chemical	CAS No.	Wt%	Final RQ Lbs
Aliphatic Petroleum Solvent	64742-89-8	60-65	100
Xylene	1330-20-7	<1	100

**CALIFORNIA PROPOSITION 65:**

This product may contain trace quantities of the following chemicals that are identified by the State of California under the Safe Drinking Water and Toxic Reinforcement Act of 1986 ("Proposition 65") as either a carcinogenic or reproductive hazard:

Chemical	CAS No.	Estimated Concentration %
Petroleum Asphalt	8052-42-4	35-45

**SECTION 16: OTHER INFORMATION**

Although the information contained herein is believed to be reliable, it is furnished without warranty of any kind. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, and storage.