

# MATERIAL SAFETY DATA SHEET

## DAUBERT CHEMICAL COMPANY

4700 SOUTH CENTRAL AVENUE  
CHICAGO, ILLINOIS 60638  
TELEPHONE: (708) 496-7350  
FAX: (708) 496-7367

EMERGENCY CONTACT:  
CHEMTREC (800) 424-9300

## HMIS HAZARD RATING

|                     |   |
|---------------------|---|
| HEALTH              | 1 |
| FIRE                | 2 |
| REACTIVITY          | 0 |
| PERSONAL PROTECTION | X |

Date of Review:

Date of Preparation: May 14, 2010

Revised:

By: M. Longo

### SECTION I: CHEMICAL IDENTIFICATION

Product Name: **TECTYL® 1506**  
General or Generic ID: Solvent Based Rust Preventive

### SECTION II: HAZARDOUS INGREDIENTS

| Component  | Wt%   | Recommended Exposure Limits (TWA)               |
|--|-------|---|
| Aliphatic Hydrocarbons (Stoddard Type)<br>CAS #8052-41-3 | 47-53 | OSHA PEL: 100 ppm TWA<br>ACGIH TLV: 100 ppm TWA |

### SECTION III: HAZARDS IDENTIFICATION

**Eye:** Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

**Skin:** May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, and skin burns. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

**Swallowing:** Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can enter the lungs during swallowing or vomiting and cause lung inflammation and/or damage.

**Inhalation:** Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms usually occur at air concentrations higher than the recommended exposure limits (See Section 8).

**Symptoms of Exposure:** Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness).

**Target Organ Effects:** Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans, and may aggravate preexisting disorders of these organs: central nervous system effects.

**Developmental Information:** No data

**Cancer Information:** No data

**Other Health Effects:** No data

**Primary Route(s) of Entry:** Inhalation, Skin absorption, Skin contact, Eye contact.

## SECTION IV: FIRST AID MEASURES

**Eyes:** If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

**Skin:** Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

**Swallowing:** Do not induce vomiting. This material is an aspiration hazard. If individual is drowsy or unconscious, place on left side with the head down. Seek medical attention. If possible, do not leave individual unattended.

**Inhalation:** If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

**Note to Physicians:** This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 3 - Swallowing) when deciding whether to induce vomiting.

## SECTION V: FIRE FIGHTING MEASURES

**Flash Point:** > 106 °F (41.1 °C) PMCC

**Explosive Limit:** (for component) Lower 1.0 Upper 6.0 %

**Autoignition Temperature:** No data

**Hazardous Products of Combustion:** May form carbon dioxide and carbon monoxide, various hydrocarbons

**Fire and Explosion Hazards:** Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, other flames and ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

**Extinguishing Media:** Regular foam, carbon dioxide, dry chemical.

**Fire Fighting Instructions:** Water or foam may cause frothing which can be violent and possibly endanger the life of the firefighter. Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

## SECTION VI: ACCIDENTAL RELEASE MEASURES

**Small Spill:** Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical sparks. Absorb liquid on vermiculite, floor absorbent or other absorbent material.

**Large Spill:** Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams or other bodies of water. Prevent from spreading. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

## SECTION VII: HANDLING AND STORAGE

**Handling:** Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor liquid, and/or solid), all hazard precautions given in the data sheet must be observed. All five gallon pails and larger metal containers including tank cars and tank trucks should be grounded and/or bonded when material is transferred.

**Storage:** Not applicable

## SECTION VIII: EXPOSURE CONTROLS/PERSONAL PROTECTION

**Eye Protection:** Chemical splash goggles in compliance with OSHA regulations are advised~ however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

**Skin Protection:** Wear resistant gloves such as: nitrile rubber. To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

**Respiratory Protections:** If workplace exposure limit(s) of product or any component is exceeded (See Exposure Guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (consult your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

**Engineering Controls:** Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

## SECTION IX: PHYSICAL AND CHEMICAL PROPERTIES

|   |                         |
|---|-------------------------|
| <b>Boiling Point:</b> (for component)       | 315 °F (157.2 °C)       |
| <b>Vapor Pressure:</b> (for component)      | 2 mmHg                  |
| <b>Specific Vapor Density:</b>              | >1 @ AIR=1              |
| <b>Specific Gravity:</b>                    | 0.85 @ 60 °F            |
| <b>Liquid Density:</b>                      | 7.1 lbs/gal @ 77 °F     |
| <b>Percent Volatiles (Including water):</b> | 52-56                   |
| <b>Evaporation Rate:</b>                    | Slower Than Ethyl Ether |
| <b>Appearance:</b>                          | Tan colored             |
| <b>State:</b>                               | Liquid                  |
| <b>Odor:</b>                                | Petroleum Solvent       |
| <b>Ph:</b>                                  | N/A                     |

## SECTION X: STABILITY AND REACTIVITY

**Hazardous Polymerization:** Product will not undergo hazardous polymerization.

**Hazardous Decomposition:** May form: carbon dioxide and carbon monoxide, various hydrocarbons.

**Chemical Stability:** Stable.

**Incompatibility:** Avoid contact with strong oxidizing agents.

## SECTION XI: TOXICOLOGICAL INFORMATION

None known.

## SECTION XII: ECOLOGICAL INFORMATION

None known.

## SECTION XIII: DISPOSAL CONSIDERATION

**Waste Management Information:** Dispose of in accordance with all applicable local, state and federal regulations.

**SECTION XIV: TRANSPORT INFORMATION**

**DOT Information - 49 CFR 172.101**

**DOT Description:** COMBUSTIBLE LIQUID, N.C.S.,III

**Container/Mode:** DRUMS/SURFACE - NO EXCEPTIONS

**NOS Component:** PETROLEUM NAPHTHA

**RQ (Reportable Quantity) - 49 CFR 172.101:** Not applicable

**SECTION XV: REGULATORY INFORMATION**

**Volatile Organic Content: (Calculated Values)**

VOC per Gallon: <3.5 lbs/gal

**EPA Hazardous Waste Number(s) (40 CFR Part 261):**

**EPA Hazard Category (40 CFR Part 370):** FIRE  
IMMEDIATE (ACUTE)

**SARA TITLE III:**

This product contains the following TOXIC CHEMICALS subject to the Reporting Requirements of Sec. 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986, and of 40 CFR Part 372:

| Chemical | CAS No. | Wt% |
|----------|---------|-----|
| NONE     |         |     |

This product contains the following EXTREMELY HAZARDOUS SUBSTANCE(S) subject to Emergency Planning Requirements under Sec. 301-303 (40 CFR Parts 300 and 355) and Emergency Release Notification Requirements under Sec. 304:

| Chemical | CAS No. | Wt% | RQ/TPQ Lbs |
|----------|---------|-----|------------|
| NONE     |         |     |            |

This product contains the following (CERCLA LIST) HAZARDOUS SUBSTANCE(S) subject to Emergency Release Notification Requirements under Sec. 304 (40 CFR Part 302):

| Chemical | CAS No. | Wt% | Final RQ Lbs |
|----------|---------|-----|--------------|
| NONE     |         |     |              |

**CALIFORNIA PROPOSITION 65:**

This product contains trace quantities of the following chemicals that are identified by the State of California under the Safe Drinking Water and Toxic Reinforcement Act of 1986 ("Proposition 65") as either a carcinogenic or reproductive hazard.

| Chemical | CAS No. | Wt% | Final RQ Lbs |
|----------|---------|-----|--------------|
| NONE     |         |     |              |

**SECTION XVI: OTHER INFORMATION**

Although the information contained herein is believed to be reliable, it is furnished without warranty of any kind. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, and storage.