

MATERIAL SAFETY DATA SHEET

DAUBERT CHEMICAL COMPANY

4700 SOUTH CENTRAL AVENUE
CHICAGO, ILLINOIS 60638
TELEPHONE: (708) 496-7350
FAX: (708) 496-7367

EMERGENCY CONTACT:
CHEMTREC (800) 424-9300

HMIS HAZARD RATING

HEALTH	2
FIRE	1
REACTIVITY	0
PERSONAL PROTECTION	X

Date of Review: N/A

Revised: December 3, 2009

Date of Preparation: February 13, 2003

By: R. Lauterbach

SECTION 1: PRODUCT IDENTIFICATION

Product Name: TECTYL® 300G CLEAR
Chemical Family: Water, Additive Blend
Material Usage: Corrosion Preventive/ Protective coating

EMERGENCY OVERVIEW: Water-based product. Alkaline liquid; may be irritating to eyes and skin. Refer to Section 3 for health effects and to Section 5 for fire hazard data.

SECTION 2: HAZARDOUS INGREDIENTS

Component	Wt.	Recommended Exposure Limits
^[1] Ethylene Glycol Butyl Ether CAS #111-76-2	5-10	ACGIH TLV: 25 ppm OSHA PEL: 25 ppm
2-Butanol CAS #78-92-2	5-10	ACGIH TLV: 100 ppm OSHA PEL: 100 ppm
Ammonium Hydroxide CAS #1336-21-6	1-5	ACGIH TLV: 25 ppm OSHA PEL: 35 ppm
^[1] Cobalt Neodecanoate CAS #27253-31-2	<1	ACGIH TLV: None Established OSHA PEL: None Established

^[1] See Section 3

SECTION 3: HEALTH HAZARD INFORMATION

Primary Routes of Entry: Skin absorption, inhalation.

Acute Effects: May cause severe eye irritation, may cause skin irritation. Prolonged skin exposure may cause dermatitis or defecating of the skin. Breathing mists may cause pulmonary irritation.

Chronic Effects: Chronic Effects of Ethylene Glycol Butyl Ether:

Inhalation: A single prolonged (hours) excessive inhalation exposure may cause adverse effects. Excessive exposure may cause irritation to upper respiratory tract. Observations in animals include blood, kidney, lung and liver effects.

The LC50 for rats is 700 ppm in 7 hours.

Systemic & other Effects: Observations in animals include blood, kidney, lung and liver effects. Observations in animals include testicular atrophy only after repeated oral administration. Testicular atrophy has not been observed with other routes of exposure. Birth defects are unlikely. Exposures having no effect on the mother should have no effect on the fetus. Did not cause birth defects in animals; other effects were seen in the fetus only at doses which caused toxic effects to the mother. Results of mutagenicity tests in animals have been negative. Results of in vitro ("test tube") mutagenicity tests have been inconclusive.

Mineral Spirits portion of Cobalt Neodecanoate may contain a small amount of Benzene (CAS #71-43-2).

Carcinogenicity: This product contains trace ingredients that are listed as carcinogens

Pre-Existing Medical Conditions Aggravated by Exposure: Exposure may aggravate pre-existing skin or respiratory problems.

SECTION 4: FIRST AID PROCEDURES

Inhalation: Move victim to fresh air and call emergency medical care. If not breathing, give artificial respiration; if breathing is difficult, give oxygen.

Eyes: In case of contact with material, immediately flush eyes with running water for at least 15 minutes. Seek immediate medical attention.

Skin: Wash skin with soap and water. Remove and isolate contaminated clothing and shoes at the site.

Ingestion: DO NOT INDUCE VOMITING. Consult a physician. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs.

SECTION 5: FIRE AND EXPLOSION HAZARD DATA

Flash Point: 136 °F (58 °C)

Explosive Limits: LEL = Not Determined UEL = Not Determined

EXTINGUISHING MEDIA: Small Fires: Dry chemical, CO₂, water spray, or regular foam. Large Fires: Water spray, fog, or regular foam. Move container from fire area if you can do it without risk. Apply cooling water to sides of containers that are exposed to flames until well after fire is out.

Special Firefighting Protection/Emergency Action: Fire may produce irritating or poisonous gases. Positive pressure self-contained breathing apparatus (SCBA) and structural firefighters' protective clothing will provide limited protection.

Unusual Fire/Explosion Hazards: None

Products of Combustion: Carbon monoxide, carbon dioxide, miscellaneous hydrocarbons.

SECTION 6: SPECIAL PRECAUTIONS AND SPILL/LEAK PROCEDURES

Steps to be taken in case Material is Released or Spilled: Shut off ignition sources; no flares, smoking or flames in hazard area. Stop leak if you can do it without risk.

Small Spills: Take up with sand or other noncombustible absorbent material and place into containers for later disposal.

Large Spills: Dike far ahead of liquid spill for later disposal.

SECTION 7: SAFE HANDLING INFORMATION

Precautions To Be Taken In Handling/Storage: Store in cool, well-ventilated area. Keep away from flames, sparks or hot surfaces. Never use a torch to cut or weld on or near container. Empty containers can contain explosive vapors.

Other Precautions: Never wear contaminated clothing. Launder or dry-clean before wearing. Discard oil-soaked shoes. Wash thoroughly with soap and water (waterless hand cleaner may be helpful in removing residues) after use and before smoking or eating. Avoid excessive skin contact.

SECTION 8: EXPOSURE CONTROLS

Respiratory Protection: NIOSH-approved respirator for organic vapor and mist to control exposure where ventilation is inadequate.

Ventilation: General and local exhaust.

Personal Protective Equipment: Protective Gloves: Impervious gloves (Viton, PVOH, etc.). Eye Protection: Safety glasses with sideshields or chemical goggles. Other Protective Clothing or Equipment: If splashing is anticipated, wear rubber apron and boots or other protective equipment to minimize contact.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Color: Amber

Appearance: Liquid

Odor: Ammonical

Boiling Point (initial): 212°F.

Evaporation Rate (water =1): 1

Vapor Pressure (mmHg @ 20°C): Not Determined

Vapor Density (air=1): >1

Solubility in Water: Miscible

Specific Gravity: 1.01

pH: 8.6

Percent Volatile by Volume: 78.00

SECTION 10: REACTIVITY HAZARD DATA

Stability: Stable

Incompatibility: Strong acids, oxidizing agents.

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, miscellaneous hydrocarbons.

Hazardous Polymerization: Will not occur.

SECTION 11: TOXICOLOGICAL INFORMATION

None Known.

SECTION 12: ECOLOGICAL INFORMATION

None Known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Methods: Dispose of in accordance with state, local and federal regulations. Materials may become a hazardous waste through use. If permitted, incineration may be practiced. Consider recycling solvent.

SECTION 14: TRANSPORTATION INFORMATION

***** EXPORT AND AIR TRANSPORTATION *****

UN1268, PETROLEUM DISTILLATES N.O.S., (Naphtha Solvent), 3, PGIII

DOMESTIC BY GROUND:

NON-REGULATED

SECTION 15: REGULATORY INFORMATION

Volatile Organic Content: (Calculated Values)

VOC per gallon: 1.32 lbs. /gal
VOC per gallon minus exempt solvents & water: 3.28 lbs. /gal

EPA Hazardous Waste Number(s) (40 CFR Part 261): D001

EPA Hazard Category (40 CFR Part 370): IMMEDIATE
DELAYED
FIRE (COMBUSTIBLE)

SARA TITLE III:

This product contains the following TOXIC CHEMICALS subject to the Reporting Requirements of Sec. 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986, and of 40 CFR Part 372:

Chemical	CAS No.	Wt.%
Ethylene Glycol Butyl Ether	111-76-2	5-10
2-Butanol	78-92-2	1-5
Cobalt Neodecanoate	27253-31-2	<1

This product contains the following EXTREMELY HAZARDOUS SUBSTANCE(S) subject to Emergency Planning Requirements under Sec. 301-303 (40 CFR Parts 300 and 355) and Emergency Release Notification Requirements under Sec. 304:

Chemical	CAS No.	Wt.%	RQ/TPQ Lbs.
None			

This product contains the following (CERCLA LIST) HAZARDOUS SUBSTANCE(S) subject to Emergency Release Notification Requirements under Sec. 304 (40 CFR Part 302):

Chemical	CAS No.	Wt%	Final RQ Lbs.
2-Butanol	78-92-2	1-5	1000
Ammonium Hydroxide	1336-21-6	1-5	1000

CALIFORNIA PROPOSITION 65:

This product contains ingredients that are identified by the State of California under the Safe Drinking Water and Toxic Reinforcement Act of 1986 ("Proposition 65") as either a carcinogenic or reproductive hazard:

SECTION 16: OTHER INFORMATION

Although the information contained herein is believed to be reliable, it is furnished without warranty of any kind. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, and storage.