

MATERIAL SAFETY DATA SHEET

DAUBERT CHEMICAL COMPANY

4700 SOUTH CENTRAL AVENUE
CHICAGO, ILLINOIS 60638
TELEPHONE: (708) 496-7350
FAX: (708) 496-7367

EMERGENCY CONTACT:
CHEMTREC (800) 424-9300

HMIS HAZARD RATING

| | |
|---------------------|---|
| HEALTH | 1 |
| FIRE | 1 |
| REACTIVITY | 0 |
| PERSONAL PROTECTION | D |

Date of Review:

Date of Preparation: July 30, 2004

Revised: March 3, 2010

By: M. Longo

SECTION I: PRODUCT IDENTIFICATION

Product Name: **TECTYL® 5187**
Chemical Family: Water, Additive Blend
Material Usage: Corrosion Preventive

EMERGENCY OVERVIEW: Water-based product. Alkaline liquid; may be irritating to eyes and skin. Refer to Section 3 for health effects and to Section 5 for fire hazard data.

SECTION II: HAZARDOUS INGREDIENTS

| Component | Wt% | Recommended Exposure Limits (TWA) |
|---|-------|--|
| Slack Wax (petroleum) CAS #64742-61-6 | 10-15 | OSHA PEL: None Established ACGIH TLV: 5 mg/m ³ (fumes) |
| ¹ Dimethyl Amino Ethanol CAS #108-01-0 | 1-2 | None Established |
| Petroleum Oil (Severely solvent refined and/or severely hydrotreated) CAS #64742-53-6 and/or 64741-97-5 | 2-4 | OSHA PEL: None Established ACGIH TLV: 5 mg/m ³ (mists) |
| Fatty Acids, Coco CAS #61788-47-7 | 2-4 | OSHA PEL: 5 mg/m ³ (oil mist) ACGIH TLV: 5 mg/m ³ (oil mist) |
| Fatty Acids, C ₁₆₋₁₈ CAS #68955-98-6 | 1-2 | OSHA PEL: 5 mg/m ³ (oil mist) ACGIH TLV: 5 mg/m ³ (oil mist) |
| Sodium Petroleum Sulfonate CAS #68608-26-4 | 2-4 | OSHA PEL: 5 mg/m ³ (oil mist) ACGIH TLV: 5 mg/m ³ (oil mist) |
| ^[1] Carbon Black CAS #1333-86-4 | 1-2 | ACGIH TLV: 3.5 mg/m OSHA PEL: 3.5 mg/m ³ (^[2] nuisance dust) |
| Ethylbenzene CAS #100-41-4 | 1-2 | OSHA PEL: None Established ACGIH TLV: None Established |

^[1] See Section 3

^[2] This component poses a hazard only if a dust is formed, i.e., by sawing, sanding, drilling, etc.

SECTION III: HEALTH HAZARD INFORMATION

Primary Routes of Entry: Skin absorption, inhalation.

Acute Effects: May cause severe eye irritation and reversible skin irritation. Prolonged skin exposure may cause dermatitis or oil acne. Breathing mists may cause pulmonary irritation or dizziness. Excessive inhalation may produce dizziness, nausea, headache, and incoordination.

Chronic Effects: Exposure to relatively high dimethylaminoethanol vapor concentrations may cause minor transient edema of the corneal epithelium. This condition, referred to as "glauropsia," "blue haze," or "blue-gray haze," produces a blurring of vision against a general bluish haze and the appearance of halos around bright objects. The effect disappears spontaneously within a few hours of the end of an exposure and leaves no sequelae. Although not detrimental to the eye per se, glauropsia predisposes an affected individual to physical accidents and reduces the ability to undertake skilled tasks, such as driving a motorized vehicle.

Carcinogenicity: Carbon Black has been classified by IARC as a Category 2B (known animal carcinogen, possible human carcinogen) material. This was based on the results of rat inhalation studies of carbon black, despite the lack of parallel evidence on humans or other animal species.

Pre-Existing Medical Conditions Aggravated by Exposure: Exposure may aggravate pre-existing respiratory or skin problems.

SECTION IV: FIRST AID PROCEDURES

Inhalation: Move victim to fresh air and call emergency medical care. If not breathing, give artificial respiration; if breathing is difficult, give oxygen.

Eyes: In case of contact with material, immediately flush eyes with running water for at least 15 minutes. Seek immediate medical attention.

Skin: Wash skin with soap and water. Remove and isolate contaminated clothing and shoes at the site.

Ingestion: DO NOT INDUCE VOMITING. Consult a physician. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs.

SECTION V: FIRE AND EXPLOSION HAZARD DATA

Flash Point:

Not Applicable (Water Based Fluid)

Explosive Limits:

LEL = Not Determined UEL = Not Determined

EXTINGUISHING MEDIA:

Small Fires: Dry chemical, CO₂, water spray, or regular foam.

Large Fires: Water spray, fog, or regular foam.

Special Firefighting Protection/Emergency Action: Fire may produce irritating or poisonous gases. Positive pressure self-contained breathing apparatus (SCBA) and structural firefighters' protective clothing will provide limited protection. If runoff from fire control occurs, notify the appropriate authorities.

Unusual Fire/Explosion Hazards: None

Products of Combustion: Carbon monoxide, carbon dioxide, miscellaneous hydrocarbons.

SECTION VI: SPECIAL PRECAUTIONS AND SPILL/LEAK PROCEDURES

Steps to be taken in case Material is Released or Spilled: Shut off ignition sources; no flares, smoking or flames in hazard area. Stop leak if you can do it without risk.

Small Spills: Take up with sand or other noncombustible absorbent material and place into containers for later disposal.

Large Spills: Dike far ahead of liquid spill for later disposal.

SECTION VII: SAFE HANDLING INFORMATION

Precautions To Be Taken In Handling/Storage: Store in cool, well-ventilated area. Keep away from flames, sparks or hot surfaces. Never use a torch to cut or weld on or near container. Empty containers can contain explosive vapors.

Other Precautions: Never wear contaminated clothing. Launder or dry clean before wearing. Discard oil-soaked shoes. Wash thoroughly with soap and water (waterless hand cleaner may be helpful in removing residues) after use and before smoking or eating. Avoid excessive skin contact.

SECTION VIII: EXPOSURE CONTROLS

Respiratory Protection: NIOSH-approved respirator for organic vapor and mist to control exposure where ventilation is inadequate.

Ventilation: General and local exhaust.

Personal Protective Equipment:

Protective Gloves: Impervious gloves (Viton, PVOH, etc.)

Eye Protection: Safety glasses with sideshields or chemical goggles.

Other Protective Clothing or Equipment: If splashing is anticipated, wear rubber apron and boots or other protective equipment to minimize contact.

SECTION IX: PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--------------------------------|----------------|
| Color: | Black |
| Appearance: | Viscous Liquid |
| Odor: | Ammonia |
| Boiling Point (initial): | 212 °F |
| Evaporation Rate (water=1): | 1 |
| Vapor Pressure (mmHg @ 20 °C): | Not Determined |
| Vapor Density (air=1): | >1 |
| Solubility in Water: | Miscible |
| Specific Gravity: | 0.97 |
| pH: | 8-10 |
| Percent Volatile by Volume: | 58 |

SECTION X: REACTIVITY HAZARD DATA

Stability: Stable

Incompatibility: Strong acids, oxidizing agents.

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, miscellaneous hydrocarbons.

Hazardous Polymerization: Will not occur.

SECTION XI: TOXICOLOGICAL INFORMATION

None known.

SECTION XII: ECOLOGICAL INFORMATION

None known.

SECTION XIII: DISPOSAL CONSIDERATIONS

Waste Disposal Methods: Dispose of in accordance with State, Local and Federal regulations. Materials may become a hazardous waste through use. If permitted, incineration may be practiced. Consider recycling solvent.

SECTION XIV: TRANSPORTATION INFORMATION

Rust Inhibitor / Non-Hazardous

SECTION XV: REGULATORY INFORMATION

Volatile Organic Content: (Calculated Values)
VOC per gallon minus exempt solvents & water: 0.5 lbs/gal

EPA Hazardous Waste Number(s) (40 CFR Part 261): Not Applicable

EPA Hazard Category (40 CFR Part 370): DELAYED (CHRONIC)

SARA TITLE III:

This product contains the following TOXIC CHEMICALS subject to the Reporting Requirements of Sec. 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986, and of 40 CFR Part 372:

| Chemical | CAS No. | Wt% |
|------------------|-----------|-----------------|
| Barium Compounds | 7440-39-3 | 0.2 (as barium) |
| Ethylbenzene | 100-41-4 | 1-2 |

This product contains the following EXTREMELY HAZARDOUS SUBSTANCE(S) subject to Emergency Planning Requirements under Sec. 301-303 (40 CFR Parts 300 and 355) and Emergency Release Notification Requirements under Sec. 304:

| Chemical | CAS No. | Wt% | RQ/TPQ Lbs |
|----------|---------|-----|------------|
| None | | | |

This product contains the following (CERCLA LIST) HAZARDOUS SUBSTANCE(S) subject to Emergency Release Notification Requirements under Sec. 304 (40 CFR Part 302):

| Chemical | CAS No. | Wt% | Final RQ Lbs |
|----------|---------|-----|--------------|
| None | | | |

CALIFORNIA PROPOSITION 65:

This product contains chemicals that are identified by the State of California under the Safe Drinking Water and Toxic Reinforcement Act of 1986 ("Proposition 65") as either a carcinogenic or reproductive hazard.

SECTION XVI: OTHER INFORMATION

Although the information contained herein is believed to be reliable, it is furnished without warranty of any kind. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, and storage.