

# MATERIAL SAFETY DATA SHEET

## DAUBERT CHEMICAL COMPANY

4700 SOUTH CENTRAL AVENUE  
CHICAGO, ILLINOIS 60638  
TELEPHONE: (708) 496-7350  
FAX: (708) 496-7367

EMERGENCY CONTACT:  
CHEMTREC (800) 424-9300

## HMIS HAZARD RATING

HEALTH	1
FIRE	2
REACTIVITY	0
PERSONAL PROTECTION	D

Date of Review:  
Date of Preparation: January 7, 1997

Revised: April 4, 2011  
By: R. Lauterbach

### SECTION I: PRODUCT IDENTIFICATION

Product Name: **TECTYL® 609**  
General or Generic ID: Petroleum Based Rust Preventive

### SECTION II: HAZARDOUS INGREDIENTS

<u>Component</u>	<u>Wt. %</u>	<u>Recommended Exposure Limits</u>
Petroleum Wax CAS #63231-60-7	7-17	None Established
Polyethylene Wax CAS #68441-17-8	7-17	None Established
Aromatic Petroleum Distillates CAS #64742-95-6	6-16	None Established
Quaternary Ammonium Compound Of Bentonite CAS #1302-78-9	1-7	None Established
Hydrotreated light distillates (petroleum) CAS #64741-47-8	54-64	OSHA PEL: 5 mg/m <sup>3</sup> ACGIH TLV: 5 mg/m <sup>3</sup>
Calcium Dinonylnaphthalene Sulfonate (P) CAS #57855-77-3	1-6	None Established
1, 2, 4-Trimethylbenzene CAS #95-63-6	2.5-3.5	None Established

### SECTION III: HAZARDS IDENTIFICATION

**Eye:** Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

**Skin:** May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, and skin burns

**Swallowing:** Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can enter the lungs during swallowing or vomiting and cause lung inflammation and/or damage.

**Inhalation:** Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful.

**Symptoms of Exposure:** Stomach or intestinal upset (nausea, vomiting, diarrhea) irritation (nose, throat, airways) , central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), and death.

**Target Organ Effects:** Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans, and may aggravate pre-existing disorders of these organs: central nervous system effects.

**Developmental Information:** No data

**Cancer Information:** No data

**Other Health Effects:** No data

**Primary Route(s) of Entry:** Inhalation, Skin contact.

#### SECTION IV: FIRST AID MEASURES

**Eyes:** If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

**Skin:** Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

**Swallowing:** Do not induce vomiting. This material is an aspiration hazard. If individual is drowsy or unconscious, place on left side with the head down. Seek medical attention. If possible, do not leave individual unattended.

**Inhalation:** If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

**Note to Physicians:** No data

#### SECTION V: FIRE FIGHTING MEASURES

**Flash Point:** 106 °F (41.1 °C) PMCC

**Explosive Limit:** (for component) Lower 1.0 Upper 6.0 %

**Autoignition Temperature:** No data

**Hazardous Products of Combustion:** May form: carbon dioxide and carbon monoxide, various hydrocarbons.

**Fire and Explosion Hazards:** Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, other flames and ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

**Extinguishing Media:** regular foam, carbon dioxide, dry chemical.

**Fire Fighting Instructions:** Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

#### SECTION VI: ACCIDENTAL RELEASE MEASURES

**Small Spill:** Absorb liquid on vermiculite, floor absorbent, or other absorbent material and transfer to hood.

**Large Spill:** Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams or other bodies of water. Prevent from spreading. If run-off occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product.

Transfer contaminated absorbent, soil and other materials to containers for disposal. Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

#### SECTION VII: HANDLING AND STORAGE

**Handling:** Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid); all hazard precautions given in the data sheet must be observed. All five gallon pails and larger metal containers including tank cars and tank trucks should be grounded and/or bonded when material is transferred.

**Storage:** Not applicable

## SECTION VIII: EXPOSURE CONTROLS/PERSONAL PROTECTION

**Eye Protection:** Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

**Skin Protection:** Wear resistant gloves such as: nitrile rubber. To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

**Respiratory Protections:** If workplace exposure limit(s) of product or any component is exceeded (See Exposure Guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control.

OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (consult your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

**Engineering Controls:** Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

## SECTION IX: PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point (for component):	355 °F (179.4 °C) @ 760 mmHg
Vapor Pressure (for component):	.5 mmHg @ 68 °F
Specific Vapor Density:	No data
Specific Gravity:	.83 @ 60 °F
Liquid Density:	6.9 lbs/gal @ 77 °F
	.83 Kg/l @ 15.6 °C
Percent Volatiles (Including Water):	70 – 72 %
Volatile Organic Compounds (VOC) (Calculated):	580 g/l
	4.8 lbs/gal
Evaporation Rate:	SLOWER THAN ETHYL ETHER
Appearance:	TRANSLUCENT
State:	SEMISOLID
Physical Form:	WAX
Color:	No data
Odor:	No data
pH:	No data
Viscosity:	6500 cps @ #5 spindle @ 10 rpm

## SECTION X: STABILITY AND REACTIVITY

**Hazardous Polymerization:** Product will not undergo hazardous polymerization.

**Hazardous Decomposition:** May form: carbon dioxide and carbon monoxide, various hydrocarbons.

**Chemical Stability:** Stable.

**Incompatibility:** Avoid contact with: strong oxidizing agents.

## SECTION XI: TOXICOLOGICAL INFORMATION

None known.

## SECTION XII: ECOLOGICAL INFORMATION

None known.

## SECTION XIII: DISPOSAL CONSIDERATION

**Waste Management Information:** Dispose of in accordance with all applicable local, state and federal regulations.

**SECTION XIV: TRANSPORT INFORMATION**

Shipping by ground – Domestically

CORROSION PREVENTIVE – Not Regulated

Shipping by Air, Overseas or Bulk Containers by any mode:

PETROLEUM DISTILLATES N.O.S., (Asphalt, Naphtha Solvent), 3, UN1268, PGIII - Flash Point 106 °F

**SECTION XV: REGULATORY INFORMATION**

**Volatile Organic Content: (Calculated Values)**

VOC per gallon: 4.8 lbs. /gal

**EPA Hazardous Waste Number(s) (40CFR Part 261):** N/A

**EPA Hazard Category (40CFR Part 370):** IMMEDIATE (ACUTE)  
FIRE (COMBUSTIBLE)

US Federal Regulations

TSCA (Toxic Substances Control Act) Status

TSCA (UNITED STATES) The intentional ingredients of this product are listed.

**SARA TITLE III**

This product contains the following TOXIC CHEMICALS subject to the *Reporting Requirements of Sec. 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986, and of 40CFR Part 372:*

CHEMICAL	CAS NO.	WT %
----------	---------	------

NONE

This product contains the following EXTREMELY HAZARDOUS SUBSTANCE(S) subject to the *Emergency Planning Requirements under Sec. 301-303 (40CFR Parts 300 and 355) and Emergency Release Notification Requirements under Sec. 304:*

CHEMICAL	CAS NO.	WT %	RQ/TPQ Lbs
----------	---------	------	------------

NONE

(CERCLA LIST) This product contains the following HAZARDOUS SUBSTANCE(S) subject to *Emergency Release Notification Requirements under Sec. 304 (40 CFR Part 302):*

CHEMICAL	CAS NO.	WT %	Final RQ Lbs
----------	---------	------	--------------

NONE

**CALIFORNIA PROPOSITION 65**

This product may contain trace quantities of the following chemicals that are identified by the State of California under the Safe Drinking Water and Toxic Reinforcement Act of 1986 ("Proposition 65") as either a carcinogenic or reproductive hazard:

CHEMICAL	CAS NO.	Estimated Concentration %
----------	---------	---------------------------

NONE

**SECTION XVI: OTHER INFORMATION**

Although the information contained herein is believed to be reliable, it is furnished without warranty of any kind. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, and storage.