

# MATERIAL SAFETY DATA SHEET

## DAUBERT CHEMICAL COMPANY

4700 SOUTH CENTRAL AVENUE  
CHICAGO, ILLINOIS 60638  
TELEPHONE: (708) 496-7350  
FAX: (708) 496-7367

EMERGENCY CONTACT:  
CHEMTREC (800) 424-9300

## HMIS HAZARD RATING

Health	1
Fire	2
Reactivity	0
Personal Protection	D

Date of Review: January 6, 2009

Revised: January 20, 2010

Date of Preparation: November 25, 2002

By: R. Lauterbach

## SECTION 1: PRODUCT IDENTIFICATION

Product Name: **TECTYL® 861 SGD**  
Material Usage: **PETROLEUM BASED RUST PREVENTATIVE**

## SECTION 2: HAZARDOUS INGREDIENTS

Component	Wt%	Recommended Exposure Limits (TWA)
Aliphatic Hydrocarbons (Stoddard Type) CAS #8052-41-3	81-91	OSHA PEL: 100 ppm ACGIH TLV: 100 ppm
Hydrotreated Naphthenic Base Oil CAS #64742-52-5	2.9-13	OSHA PEL: 5 mg/m <sup>3</sup> ACGIH TLV: 5 mg/m <sup>3</sup>
Sodium Petroleum Sulfonate CAS #68608-26-4	1-9	None Established
Odor Masking Agent CAS # N/A	0.1	None Established

## SECTION 3: HEALTH HAZARD INFORMATION

**Eyes:** Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

**Skin:** May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, and skin burns

**Swallowing:** Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can enter the lungs during swallowing or vomiting and cause lung inflammation and/or damage.

**Inhalation:** Breathing of vapor or mist is possible. Breathing small amounts of this *material* during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful.

**Symptoms of Exposure:** stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), and death.

**Target Organ Effects:** Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans, and may aggravate pre-existing disorders of these organs: central nervous system effects.

**Developmental Information:** No data

**Cancer Information:** No data

**Other Health Effects:** No data

**Primary Route(s) of Entry:** Inhalation, Skin contact.

#### SECTION 4: FIRST AID PROCEDURES

**Eyes:** If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

**Skin:** Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

**Swallowing:** Do not induce vomiting. This material is an aspiration hazard. If individual is drowsy or unconscious, place on left side with the head down. Seek medical attention. If possible, do not leave individual unattended.

**Inhalation:** If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

**Note to Physicians:** No data

#### SECTION 5: FIRE AND EXPLOSION HAZARD DATA

**Flash Point:** 104 °F (40 °C) PMCC

**Explosive Limit:** (for component) Lower 1.0 Upper 6.0 ¾

**Autoignition Temperature:** No data

**Hazardous Products of Combustion:** May form: carbon dioxide and carbon monoxide, various hydrocarbons.

**Fire and Explosion Hazards:** Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, other flames and ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

**Extinguishing Media:** regular foam, carbon dioxide, dry chemical.

**Fire Fighting Instructions:** Water or foam may cause frothing which can be violent and possibly endanger the life of the firefighter. Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

#### SECTION 6: SPECIAL PRECAUTIONS AND SPILL/LEAK PROCEDURES

**Small Spill:** Absorb liquid on vermiculite, floor absorbent, or other absorbent material and transfer to hood.

**Large Spill:** Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams or other bodies of water. Prevent from spreading. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal. Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

## SECTION 7: SAFE HANDLING INFORMATION

**Handling:** Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

**Storage:** Not applicable

## SECTION 8: EXPOSURE CONTROLS

**Eye Protection:** Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

**Skin Protection:** Wear resistant gloves such as: nitrile rubber, to prevent repeated or prolonged skin contact, wear impervious clothing and boots.

**Respiratory Protections:** If workplace exposure limit(s) of product or any component is exceeded (See Exposure Guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (consult your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

**Engineering Controls:** Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

<b>Boiling Point: (for component)</b>	315 °F (157.2 °C)
<b>Vapor Pressure:</b>	2 mmHg
<b>Specific Vapor Density:</b>	>1 @ AIR =1
<b>Specific Gravity:</b>	.78 @ 77 °F
<b>Liquid Density:</b>	6.5 lbs/gal @ 77 °F
<b>Percent Volatiles (Including Water):</b>	90-96
<b>Evaporation Rate:</b>	SLOWER THAN ETHYL ETHER
<b>Appearance:</b>	Transparent
<b>State:</b>	LIQUID
<b>Physical Form:</b>	No data
<b>Color:</b>	UNKNOWN
<b>Odor:</b>	No data
<b>pH:</b>	Not Applicable

## SECTION 10: REACTIVITY HAZARD DATA

**Hazardous Polymerization:** Product will not undergo hazardous polymerization.

**Hazardous Decomposition:** May form: carbon dioxide and carbon monoxide, various hydrocarbons.

**Chemical Stability:** Stable.

**Incompatibility:** Avoid contact with: strong oxidizing agents.

## SECTION 11: TOXICOLOGICAL INFORMATION

None known.

## SECTION 12: ECOLOGICAL INFORMATION

None known.

**SECTION 13: DISPOSAL CONSIDERATIONS**

**Waste Management Information:** Destroy by liquid incineration. Dispose of in accordance with all applicable local, state and federal regulations.

**SECTION 14: TRANSPORTATION INFORMATION**

\*\*\*\*\* EXPORT AND AIR TRANSPORTATION \*\*\*\*\*

**UN1268, PETROLEUM DISTILLATES N.O.S., (Naphtha Solvent), 3, PGIII**

**DOMESTIC BY GROUND:**

**NON-REGULATED**

**SECTION 15: REGULATORY INFORMATION**

**Volatile Organic Content: (Calculated Values)**

VOC per gallon: 5.9 lbs/gal

**EPA Hazardous Waste Number(s) (40 CFR Part 261):** N/A

**EPA Hazard Category (40 CFR Part 370):** IMMEDIATE (ACUTE)  
FIRE

**SARA TITLE III:**

This product contains the following TOXIC CHEMICALS subject to the Reporting Requirements of Sec. 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986, and of 40 CFR Part 372:

Chemical	CAS No.	Wt%
NONE		

This product contains the following EXTREMELY HAZARDOUS SUBSTANCE(S) subject to Emergency Planning Requirements under Sec. 301-303 (40 CFR Parts 300 and 355) and Emergency Release Notification Requirements under Sec. 304:

Chemical	CAS No.	Wt%	RQ/TPQ Lbs
NONE			

This product contains the following (CERCLA LIST) HAZARDOUS SUBSTANCE(S) subject to Emergency Release Notification Requirements under Sec. 304 (40 CFR Part 302):

Chemical	CAS No.	Wt%	Final RQ Lbs
NONE			

**CALIFORNIA PROPOSITION 65:**

This product may contain trace quantities of the following chemicals that are identified by the State of California under the Safe Drinking Water and Toxic Reinforcement Act of 1986 ("Proposition 65") as either a carcinogenic or reproductive hazard:

Chemical	CAS No.	Estimated Concentration %
NONE		

**SECTION 16: OTHER INFORMATION**

Although the information contained herein is believed to be reliable, it is furnished without warranty of any kind. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, and storage.