
**PRODUCT
INFORMATION****PIONEER 68****Asphalt Paint****Description**

PIONEER 68 asphalt paint is an all-purpose protective paint specially developed for low-cost maintenance of metal surfaces and structures.

This material is excellent for water resistance and is useful as general protective coatings for metal work, such as structural steel, storage tanks, pipes and fittings, automotive replacement parts and springs.

Dried films of the bright black coating will withstand the action of picric, sulfuric, nitric and hydrochloric acids for 6 hours without disintegration, browning, or dulling. Also, dried films of the paint will neither sag nor flow when heated to 200 deg F. for one hour.

Can be used effectively as a concrete curing compound and as a blending base for paints, enamels and japans.

May be applied directly to clean and dry surfaces by spray, brush, or dipcoating operations.

Physical Properties

	Typical Values
Color	Black
Solids Content	50%
Solvent Content	50%
Penetration @ 77 deg F. (Base)	5-10
Melting Point (Base)	210-220 deg F.
Drying Time: Dust Free (minutes)	15 (max.)
Drying Time: Tack Free (minutes)	30 (max.)
Method of Application	Spray, Dip, Brush, or Roller Coat
Coverage Sq Ft/Gal	300-350
Flash Point, (deg. F.)	50 (min.)

June 22, 2010:kc

CAUTION: The data, statements and recommendations set forth in this product information sheet are based on testing, research and other development work which has been carefully conducted by us, and we believe such data, statements and recommendations will serve as reliable guidelines. However, this product is subject to numerous uses under varying conditions over which we have no control, and accordingly, we do NOT warrant that this product is suitable for any particular use. Users are advised to test the product in advance to make certain it is suitable for their particular production conditions and particular use or uses.

WARRANTY: Daubert Chemical Company, Inc. ("Daubert") warrants all products manufactured by it to be free from defects in material and workmanship. DAUBERT MAKES NO OTHER WARRANTIES, WHETHER, EXPRESSED OR IMPLIED, WITH RESPECT TO SUCH PRODUCTS, AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND IMPLIED WARRANTIES ARISING FROM A COURSE OF DEALING OR USAGE OF TRADE, ARE DISCLAIMED BY DAUBERT. All claims hereunder must be made in writing within 30 days after receipt of the products at the buyer's plant and prior to further processing the products or combining them with other materials or products. Daubert's liability, whether under this warranty or in contract, tort, negligence or otherwise, is limited to the return of the net purchase price paid for any products proven defective or, at Daubert's option, to the repair or replacement of said products upon their return, transportation prepaid, to Daubert. THE REMEDY HEREBY PROVIDED SHALL BE THE EXCLUSIVE AND SOLE REMEDY OF THE BUYER, AND UNDER NO CIRCUMSTANCES SHALL DAUBERT BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES. No Daubert representative or other person is authorized to change this warranty in any way or to assume for Daubert any other liability in connection with the sale or use of its products.

REFER TO MATERIAL SAFETY DATA SHEET FOR HEALTH AND SAFETY INFORMATION.

DAUBERT
CHEMICAL COMPANY, INC.

PAGE 2 OF 2

4700 South Central Avenue ■ Chicago, IL 60638 ■ 1-800-688-0459 ■ or 708-496-7350 ■ Fax: 708-496-7367

Visit our web site at www.daubert.com ■ Our e-mail is dauchem@daubert.com

